

Hardware Fittings — Forged Steel

A
19

Chain Links

FORGED STEEL

LK



Type LK8



Type LK8T

Links are used to maintain proper tower clearance and connect associated hardware within an insulator string.

Material: Body – galvanized steel




Figure 1




Figure 2




Figure 3

Product Data

Catalog Number	Figure Number	Ultimate Strength lb (kN)	Dimensions Inches mm)					Approx Wt Each lb (kg)
			L	A	B	W	T	
LK30	1	30,000 (133)	2¼ (57.2)	—	½ (12.7)	1 (25.4)	½ (12.7)	.44 (.20)
LK60	1	60,000 (267)	3½ (88.9)	—	¾ (19.1)	1 (25.4)	¾ (19.1)	1.5 (.68)
LK80	1	80,000 (356)	4 (101.6)	—	7/8 (22.2)	1¼ (31.8)	7/8 (22.2)	2.15 (.96)
LK120CVN	1	120,000 (533)	4 (102)	—	1 (25.4)	1¼ (31.8)	1 (25.4)	3.1 (1.41)
LK150	1	150,000 (667)	5½ (139.7)	—	1¾ (34.9)	1¾ (44.5)	1¾ (34.9)	6.90 (3.13)
LK830	2	30,000 (133)	3¾ (85.7)	1½ (28.6)	—	7/8 (22.2)	9/16 (14.3)	.75 (.34)
LK830T	3	30,000 (133)	3¾ (85.7)	1½ (28.6)	—	7/8 (22.2)	9/16 (14.3)	.75 (.34)
792722000	1	45,000 (200)	3¼ (82.6)	—	11/16 (17.5)	1 (25.4)	11/16 (17.5)	.95 (.43)