

Autobahn ATB0

Autobahn LED Cobra Head



Product Submittal Description:

Autobahn Cobra Head, 88W, 12,176 Lumens nominal, 120-277V, Roadway Type V, 4000K (standard), Gray (standard), 20kV/10KA SPD (standard), Terminal block (standard), NEMA label, 3-pin photocontrol receptacle (standard), Long life photocontrol



The product images shown are for illustration purposes only and may not be an exact representation of the product.

[IES Files](#)

[BIM Models](#)

[Full Spec Sheet](#)

Product Webpage: www.acuitybrands.com/products/detail/122046

Warranty: www.acuitybrands.com/support/warranty/terms-and-conditions

Model #: **ATB0 P204 MVOLT R5 (4K) (GY) (20) (TB) NL (P3) PCLL** ✓

Series*		Performance Package*				Voltage*	
ATB0	Autobahn Cobra Head	P201	36W, 5,369 Lumens nominal	P305	145W, 19,893 Lumens nominal	347	347V
		P202	49W, 6,943 Lumens nominal	P451	105W, 16,320 Lumens nominal	480	480V
		P203	70W, 10,056 Lumens nominal	P452	125W, 19,087 Lumens nominal	MVOLT	120-277V
		P204	88W, 12,176 Lumens nominal	P453	159W, 23,592 Lumens nominal	XVOLT	277V-480V
		P205	102W, 13,737 Lumens nominal	P454	170W, 25,070 Lumens nominal		
		P301	67W, 10,367 Lumens nominal	P455	187W, 27,091 Lumens nominal		
		P302	83W, 12,185 Lumens nominal	P456	203W, 28,347 Lumens nominal		
		P303	106W, 15,351 Lumens nominal	P457	211W, 29,715 Lumens nominal		
		P304	124W, 17,714 Lumens nominal				
Distribution*		Color Temperature*		Finish*		Surge Protection*	
R2	Roadway Type II	(4K)	4000K (standard)	(GY)	Gray (standard)	(20)	20kV/10KA SPD (standard)
R3	Roadway Type III	27K	2700K	BK	Black	MP	10kV/5kA MOV pack
R3L	Type III long	3K	3000K	BZ	Bronze		
R4	Roadway Type IV	5K	5000K	DDB	Dark bronze		
R5	Roadway Type V	LWAMB	Limited Wavelength Amber	GI	Graphite		
				GN	Green		
				WH	White		
Terminal Block*		Bubble Level		Listing		Shield	
(TB)	Terminal block (standard)	BL	External Bubble Level	XL	No CSA Listing	HSS	House side shield
T2	Wired to L1 and L2 position						

Submittal Spec Sheet

Dynamically Generated

Series: ATB0

Date: 8/26/2026

Project:

Group/Type:

Qty: 0

Label	Top Receptacle*	Adjustable Output	Photocontrol
NL NEMA label	(P3) 3-pin photocontrol receptacle (standard) NR No photocontrol receptacle P7 7-pin photocontrol receptacle	AO Field adjustable output	PCLL Long life photocontrol PCSS Solid state photocontrol SH Shorting cap
Point of Manufacture	Job Pack	Packaging	
BAA Buy America(n) Act and/or Build America Buy America Qualified	JP Job pack	JP42 Job pack of 42	

This is a dynamic specification sheet that is based on certain selections made by the user. All results generated are for informational purposes only. The user should validate the results with its agency sales representative to determine whether the product has been configured correctly before ordering. Acuity Brands Lighting is not responsible for any loss resulting from product configuration errors.

Not all versions of the product are available with all options.

Specifications subject to change without notice.

Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

See the full specification sheet at the product page link above for full product information and detailed ordering information.

Certain airborne contaminants can diminish the integrity of acrylic and/or polycarbonate.

Visit: <http://www.acuitybrandslighting.com/library/ll/documents/specsheets/acrylic-polycarbonate-compatibility.pdf> for Acrylic-Polycarbonate Compatibility table for suitable uses.

All trademarks referenced are property of their respective owners.