



FIBERGLASS EQUIPMENT MOUNTS



Single Phase/Double Position 15° Mount

Material Specifications

Pole Gain


- 65-45-12 Ductile Iron, hot-dipped galvanized per ASTM A153 (6" to 8" mounting centers)
- Accepts 5/8" pole mounting hardware
- Can be banded using the Aluma-Form Bolt-A-Band banding system

End Fitting

- 65-45-12 Ductile Iron, hot-dipped galvanized per ASTM A153

Fiberglass Rod

- 1-1/2" diameter Super-Smooth, proprietary veiled gray polyester rod with added ultraviolet protection



Catalog Name	Rod Diameter	Standoff Length, A ¹	Hardware ²	Ultimate Load			Weight
				P1 (lbs)	P2 (lbs)	P3 (lbs)	
F1CA-MV-A12-D3	1-1/2"	12"	No	1,800	1,400	10,000	7.9 lbs.
F1CA-MV-A15-D3	1-1/2"	15"	No	1,500	1,150	10,000	8.3 lbs.
F1CA-MV-A18-D3	1-1/2"	18"	No	1,200	900	10,000	8.6 lbs.
F1CA-MV-A24-D3	1-1/2"	24"	No	900	700	10,000	9.4 lbs.
F1CA-MV-A12-D3-H	1-1/2"	12"	Yes	1,800	1,400	10,000	8.3 lbs.
F1CA-MV-A15-D3-H	1-1/2"	15"	Yes	1,500	1,150	10,000	8.7 lbs.
F1CA-MV-A18-D3-H	1-1/2"	18"	Yes	1,200	900	10,000	9.1 lbs.
F1CA-MV-A24-D3-H	1-1/2"	24"	Yes	900	700	10,000	9.9 lbs.

Notes:

1. Custom lengths available, contact factory or local sales representative.

2. Standard hardware includes captured 1/2" x 2" carriage bolt, 1/2" hex nut, 1/2" lock washer, & 1/2" star washer.