



* Representative image

Connector, Tank Grounding

by ANDERSON
Catalog ID: GTCL34ATP

Connector, Tank Grounding.

- High strength eyebolt installs conductor perpendicular to stud thread.

Product Details

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Cover Available	No
Inhibitor Loaded	No
Material	Bronze; Copper
Material - Body	Bronze Alloy
Material - Eyebolt	Silicon Bronze
Material - Hardware	Silicon Bronze or Stainless Steel
Number of Stud Threads	13
Product Category	Mechanical Connectors
Style	Eye Bolt
UPC	096359313779

Dimensions

Bolt Diameter	0.380 in
Diameter - Bolt	0.38 in
Diameter - Stud	0.5 in
Weight	0.294 lb

Conductor Related

Conductor Diameter - Maximum	0.419 in
Conductor Diameter - Minimum	0.128 in
Conductor Diameter Range	0.128 - 0.419

Certifications and Compliance

UL Listed	No
-----------	----

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com