



Representative

Catalog Number: K656ETP-J0270-DRG
Product ID: 7TAA122410R0146
UPC Number: 78378646987
Status: A

600 Amp, 25kV, Deadbreak Elbow, Test and Ground Replacement Kit with Test Point. Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 4/0 /Compacted Solid 250 /mmSquared Compact 125. With Insulated Cap.

North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Type	Window-Op Connector
Special Features	Capacitive Test Point, Insulated Cap
Application	600 Amps, 25kV
Standard	ANSI/IEEE Standard 386
Size	Cable Insulation Diameter 0.980 inch to 1.180 inch.
Connection	Compression
Conductor Range	4/0 STR/COMPR AWG ; 250 kcmil
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	25 kV
Amperage Rating	600 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com