Catalog No. K656ETP-M0380

Product Details



UPC: 783786950508

Details: 600 Amp, 25kV, Deadbreak Elbow, Window Op Connector Kit with Test Point. Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 700/750 /Compacted Solid 900.

Product Details

Details

Catalog No.	K656ETP-M0380
Description	600A ELBOW TAP PLUG
Std. Package Weight	1.000 LB
Product Family	9E7
Restock Fee	
Customer Reference No.	
Brand Name	ELASTIMOLD
Minimum Order Qty.	1

UPC	783786950508
GSA Compliance	No
Discount Schedule	9E
CCC	
Currency	USD
Notes	No standard price available. Book price displayed
Package Qty.	1
Country Or Territory Of Origin	United States

© 2026 ABB. ® ABB. All third-party trademarks are the property of their respective owners

Specifications

General Characteristics

Category	Electrical connector assembly
Special Features	Capacitive Test Point
Application	600 Amps, 25kV
Connection	Compression
Conductor Range	700 to 750 kcmil , 900 kcmil
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	25 kV
Amperage Rating	600 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C

Dimensions and Classifications

Brand Name	Elastimold
Standard	ANSI/IEEE Standard 386
Size	Cable Insulation Diameter 1.370 inch to 1.630 inch.

© 2026 ABB. ® ABB. All third-party trademarks are the property of their respective owners

© 2026 ABB. ® ABB. All third-party trademarks are the property of their respective owners