



21.0 A, Type Slo-Fast Fuselinks, 26" Length, Solid Head

By Chance
Catalog # [M21SF](#)

21.0 amp, Type SloFast Cutout fuselink with a 26" (660.4mm) pigtail.

Features

- Comparable to Cooper/Kearney Type X fuse links
- Compliant with ANSI/IEEE C37.42 - 2016 mechanical interchangeability requirements
- Compatible with universal style expulsion fuse holders
- Dual element design specific for tranformer protection
- Slow portion of time current characteristic curve closely mateches transformers safe loading cureve
- Individually packed for all weather protection
- Type and Current Rating on packaging and fuse for easy identification

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	Contact Manufacturer

Current

Amperage Rating	21.0 A
-----------------	--------



Dimensions

Length - Fuselink	26" (660.4mm)
Weight	0.108 lb.

General

Fuselink Type	Type SloFast
Fuse Head Style	Solid
Material type	Non-Standard
Type	Fuselinks
UPC	096359044734
Required Cutout Fuseholder	100 Amp (Do not use in a 200 amp fuseholder.)

Logistics

Standard Package	10
Pallet Quantity	4800

Product Assets

[Catalog \[English\]](#)