

Type M3 Switch DISTRIBUTION CLASS

RUS Listed

Ordering Information

M3

BASE

D = Distribution base, serrated slots with four $\frac{3}{8}$ " x 8"/10" carriage bolts and backstrap

H = Distribution base, smooth slots with four $\frac{1}{2}$ " x 8"/10" carriage bolts and backstrap

RATED CURRENT

6 = 600 AMP

9 = 900 AMP

INSULATION

2 = 15kV 110BIL Porcelain

3 = 25kV 125BIL Porcelain (not available in 900 amp)

4 = 35kV 150BIL Porcelain

6 = 15kV 110BIL Polymer

7 = 25kV 125BIL Polymer (not available in 900 amp)

8 = 35kV 150BIL Polymer

OPTIONS

C = Captive Hardware*

Consists of 4 each: $\frac{1}{2}$ " 13 stainless steel bolts, $\frac{1}{2}$ " flatwasher / lockwasher, $\frac{1}{2}$ " 13 bronze nut

L = Open Position Latch (P8070181P)

Stainless steel latch for holding the blade in the 160° open position

P = Parallel Groove Terminals* (ACT1343 2 per switch)

Two complete connectors and hardware. Accepts #2 - 500 kcmil (Copper or Aluminum)

R = Bypass Studs (P8070166P 2 per switch)

Two copper alloy bypass studs, which can be used for regulator or recloser bypassing

*NOTE: Captive Hardware and Parallel Groove Terminals CANNOT be ordered together.

BOLT LENGTH

A = 10" Length

B = 8" Length

