

Utility - Overhead Connectors

PPT - Pin Type Transformer Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Stud is tin plated copper providing low contact resistance for connection to transformer
- * Range taking design reduces inventory
- * Rated for 600 Volts

PPT250-4P
SHOWN




Catalog Number	Copper Stud Diameter	Copper Stud Length	Number of Ports	Dimensions, Inches			Wire Range KCMIL
				L	W	H	
PPT1/0-2P	3/8	3	2	2.03	0.63	0.88	1/0-#14
PPT1/0-4P	3/8	3	4	3.33			
PPT250-2P	1/2	4	2	2.59	0.88	1.13	250-#10
PPT250-3P	1/2	4	3	3.46			
PPT250-4P	1/2	4	4	4.32			
PPT250-5P	1/2	4	5	5.18			
PPT250-6P	1/2	4	6	6.04			
PPT250-8P	1/2	4	8	7.77			
PPT350-2P	5/8	4	2	2.95	0.88	1.25	350-#10
PPT350-212P	1/2	4	2	2.95			
PPT350-3P	5/8	4	3	3.95			
PPT350-312P	1/2	4	3	3.95			
PPT350-4P	5/8	4	4	4.95			
PPT350-412P	1/2	4	4	4.95			

Continued on next page

OPTIONS:

- A - Anodized set screws
- SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
- C - Connector with Black cover
- For omission of oxide inhibitor delete suffix "P"

Example:
PPT250-4SLCP



Consult factory for additional configurations not listed

Utility - Overhead Connectors

PPT - Pin Type Transformer Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Stud is tin plated copper providing low contact resistance for connection to transformer
- * Range taking design reduces inventory
- * Rated for 600 Volts

PPT250-4P
SHOWN




Catalog Number	Copper Stud Diameter	Copper Stud Length	Number of Ports	Dimensions, Inches			Wire Range KCMIL
				L	W	H	
PPT350-5P	5/8	4	5	5.95	0.88	1.25	350-#10
PPT350-512P	1/2	4	5	5.95			
PPT350-6P	5/8	4	6	6.95			
PPT350-612P	1/2	4	6	6.95			
PPT350-8P	5/8	4	8	8.95			
PPT350-812P	1/2	4	8	8.95			
PPT500-2P	3/4	4-1/2	2	3.50	1.13	1.63	500-#10
PPT500-3P	3/4	4-1/2	3	4.65			
PPT500-4P	3/4	4-1/2	4	5.79			
PPT500-5P	3/4	4-1/2	5	6.94			
PPT500-6P	3/4	4-1/2	6	8.08			
PPT500-8P	3/4	4-1/2	8	10.37			
PPT750-2P	3/4	5-1/2	2	4.04	1.25	1.75	750-1/0
PPT750-4P	3/4	5-1/2	4	6.72			

OPTIONS:

- A - Anodized set screws
- SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
- C - Connector with Black cover
- For omission of oxide inhibitor delete suffix "P"

Example:
PPT500-4SLCP



Consult factory for additional configurations not listed