

RLB750-8I

by CMC
Catalog ID: RLB750-8I



Stud-mount transformer connectors, insulated slip-fit with patented sharkbite™ mount, Dual rated connectors for Aluminum or Copper conductors

- Connector fabricated from 6061-T6 aluminum alloy for conductivity and strength.
- Supplied with aluminum radial-tipped set screws.
- Includes inhibitor in all ports and stud-mounting hole.
- Patented two-in-one Sharkbite™ mounting hole feature allows the connector to fit on a 5/8" - 11 or 1" - 14 transformer stud. Both sizes fit in the same hole.
- The Sharkbite™ feature also securely locks the connector onto the stud to eliminate wobble when installing the conductors.
- Fully tested to ANSI C119.4 for Class 'A' connectors.

Product Details

General	
Material	Aluminum Alloy, 6061-T6
UPC	192663085859

Dimensions	
Height	2.95 in
Length	14.73 in
Width	4.91 in

Electrical Ratings	
Voltage Rating	600 V

Conductor Related	
Conductor Range	750 Kcmil - #2 AWG
Number Of Conductors	8



CONNECTOR MANUFACTURING COMPANY
3501 Symmes Road
Hamilton, Ohio 45015 - 1369
513 - 860 - 4455(Press 2 for Customer Service and Sales)
To email customer Service: [jrex @cmclugs.com](mailto:jrex@cmclugs.com)

