

Aluminum Compression Terminal for 700 - 800 AL, 636 24/7, 26/7, 666.6 24/7, 715.5 36/1 ACSR, 900 COMPACT

By Anderson
Catalog # [VAUL80012BN](#)

Aluminum Compression Terminal for 700 - 800 AL, 636 24/7, 26/7, 666.6 24/7, 715.5 36/1 ACSR, 900 COMPACT

Features

- Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

Specifications

UL Listed No

Conductor

Conductor Diameter (VersaCrimp) - Maximum	1.031 in
Conductor Diameter (VersaCrimp) - Minimum	0.806 in
Conductor Compatibility	- ACSR-Lark-397.5-30/7 - ACSR-Pelican-477-18/1 - ACSR-Flicker-477-24/7 - ACSR-Hawk-477-26/7 - ACSR-Hen-477-30/7 - ACSR-Osprey-556.5-18/1 - ACSR-Parakeet-556.5-24/7 - ACSR-Dove-556.5-26/7 - ACSR-Eagle-556.5-30/7 - ACSR-Peacock-605-24/7 - ACSR-Squab-605-26/7 - ACSR-Teal-605-30/19 - ACSR-Kingbird-636-18/1 - ACSR-Swift-636-36/1 - ACSR-Rook-636-24/7 - ACSR-Grosbeak-636-26/7 - ACSR-Egret-636-30/19 - ACSR-Flamingo-666.6-24/7 - ACSR-Gannet-666.6-26/7 - AAC-Zinnia-500-19 - AAC-Hyacinth-500-37 - AAC-Dahlia-556.5-19 - AAC-Mistletoe-556.5-37 - AAC-Meadowsweet-600-37 - AAC-Orchid-636-37 - AAC-Flag-700-61 - AAC-Violet-715.5-37 - AAC-Nasturtium-715.5-61 - AAC-Cattail-750-61 - AAC-Arbutus-795-37



- AAC-Lilac-795-61
- AAC-Snapdragon-900-61
- ACAR-653.1-12/7
- ACAR-739.8-18/19

Configuration

Physical Attribute - Number of Holes	2
Number of Pad Holes	2

Dimensions

Length	7.250 in
Die Size	*See Resources / Downloads for die selection and installation instructions
Weight	0.796 lb.
Height	1.660 in
Width	1.600 in
Diameter - Pad Bolt	0.5 in
Dimension - Hole Size inch	0.500 in
Dimensions	7.250 in x 1.600 in x 1.660 in

General

Material type	Standard
Style	Impact Extruded
Color Code	None
Plating	No
UPC	096359334996
Material	Aluminum
Material - Body	Aluminum

Logistics

Carton Quantity	40
-----------------	----

Operational

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
--------------	---

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)