

## YP2U3, Figure 3-shaped Aluminum Connector with adjustable spacer

By Burndy  
Catalog # [YP2U3](#)

Wide range, universal and reversible, Figure 3 shaped aluminum connector with adjustable overhanging spacer that separates conductors, Conductor Groove A Solid: 6, 4, 3, 2.

### Features

- Wide range universal and reversible, Figure 3-shaped aluminum connector features adjustable overhanging spacer that separates conductors
- Spacer holds run or tap in place, permitting lineman to either approach the line ready to crimp or to assemble connector and tap on run and then crimp
- Massive aluminum design minimizes conductor corrosion due to galvanic action
- Pre-filled with PENETROX joint compound and stripsealed

### Application


For Copper, Aluminum Or ACSR Conductors

### Specifications

|                               |    |
|-------------------------------|----|
| Certification - UL Recognized | No |
| Buy American Compliant        | No |
| Certification - cULus         | No |
| Certification - ETL           | No |
| Standards - RoHS Compliance   | CM |
| Status                        |    |
| UL Listed                     | No |
| Certification - CSA Approved  | No |

### Conductor

|                                   |                                                                                                                                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor - AL Str Size A         | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 4 AWG</li> </ul>                                                                                      |
| Conductor - AL Str Size B         | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 4 AWG</li> </ul>                                                                                      |
| Conductor - AL Str Size A Range   | 6 AWG-4 AWG                                                                                                                                                     |
| Conductor - AL Str Size B Range   | 6 AWG-4 AWG                                                                                                                                                     |
| Conductor - ACSR Str Size A       | <ul style="list-style-type: none"> <li>• 6 (6/1) Turkey AWG</li> <li>• 5 (6/1) Thrush AWG</li> <li>• 4 (6/1) Swan AWG</li> <li>• 4 (7/1) Swanate AWG</li> </ul> |
| Conductor - ACSR Str Size B       | <ul style="list-style-type: none"> <li>• 6 (6/1) Turkey AWG</li> <li>• 5 (6/1) Thrush AWG</li> <li>• 4 (6/1) Swan AWG</li> <li>• 4 (7/1) Swanate AWG</li> </ul> |
| Conductor - ACSR Str Size A Range | 6 (6/1) Turkey AWG-4 (7/1) Swanate AWG                                                                                                                          |
| Conductor - ACSR Str Size B Range | 6 (6/1) Turkey AWG-4 (7/1) Swanate AWG                                                                                                                          |
| Conductor - Copper Str Size A     | <ul style="list-style-type: none"> <li>• 6 AWG</li> </ul>                                                                                                       |



|                                       |                                                                                                                                                                 |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor - Copper Str Size B         | <ul style="list-style-type: none"> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul> |
| Conductor - Copper Str Size A Range   | 6 AWG-3 AWG                                                                                                                                                     |
| Conductor - Copper Solid Size A       | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>                                   |
| Conductor - Copper Solid Size B       | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>                                   |
| Conductor - Copper Solid Size A Range | 6 AWG-2 AWG                                                                                                                                                     |
| Conductor - Copper Solid Size B Range | 6 AWG-2 AWG                                                                                                                                                     |
| Conductor - Copper Str Size B Range   | 6 AWG-3 AWG                                                                                                                                                     |

### Dimensions

|                                 |           |
|---------------------------------|-----------|
| Package Height                  | 0.000 in  |
| Dimension - Height inch         | 1.30 in   |
| Package Weight                  | 0.000 lb. |
| Package Length                  | 0.000 in  |
| Package Width                   | 0.000 in  |
| Dimension - L Length Overall mm | 38 mm     |
| Dimension - Width inch          | 0.72 in   |
| Dimension - Length Overall inch | 1.50 in   |

### General

|                           |                                                                               |
|---------------------------|-------------------------------------------------------------------------------|
| Product Family            | Utility Overhead & Underground Distribution>Compression Tap Connectors>C-Taps |
| Trade Name                | CABELOK™ CRIMPIT™                                                             |
| Die Index                 | O                                                                             |
| Prefilled Oxide Inhibitor | Y                                                                             |
| Plated                    | No                                                                            |
| Sub Brand                 | CABELOK CRIMPIT                                                               |

|                   |                |
|-------------------|----------------|
| Product Type      | Compression    |
| UPC               | 781810131732   |
| Type              | YP-U           |
| Material          | Aluminum       |
| Plating Type      | Unplated       |
| UPC 12 Digit      | 781810131732   |
| UPC 14 Digit GTIN | 00781810131732 |

Logistics

|                       |      |
|-----------------------|------|
| Minimum Pack Quantity | 1    |
| Pallet Quantity       | 3700 |
| Carton Quantity       | 50   |

Product Assets

[Catalog \[English\]](#)



A Hubbell brand